

MAMMUT



sandbag filling machine



the power
brand

sandbag filling machine

patent-registered outlet ports



electric drive



PTO-drive from the tractor



MAMMUT AFM 95 E 3S

- ✓ patent-registered outlet ports
- ✓ practical for wet, frozen or very rough sand
- ✓ very unsensitive stirrer
- ✓ galvanized adjustment of height of the machine for pleasant working height
- ✓ accessories as per preparation
- ✓ robust and user-friendly construction

a lot
better



Technical data

drive	electric drive 4,5 kW
drum diameter	950 mm
capacity	240 l
sacks per hour	1 500
outlet ports for the workers	3
guarantee	3 Years

Standard equipment

- protective grid on the surface of the machine
- electric drive 4,5 kW

Additional equipment

- galvanized feed hopper 4-parted 1,2 x 1,2 m

MAMMUT AFM 150 5S

- ✓ patent-registered outlet ports
 - ✓ practical for wet, frozen or very rough sand
 - ✓ very unsensitive stirrer
 - ✓ galvanized adjustment of height of the machine for pleasant working height
 - ✓ accessories as per preparation
 - ✓ robust angular gear with comfortable gear transmission ratio for calm and trouble-free work
-



Technical data

drive	PTO-drive from the tractor – optionally with electric drive 9,5 kW
drum diameter	1 500 mm
capacity	800 l
sacks per hour	3 000
outlet ports for the workers	5
guarantee	3 years

Standard equipment	Additional equipment
<ul style="list-style-type: none">• protective grid on the surface of the machine• drive with Zapfwelle vom Traktor aus• mount for forklift tines series	<ul style="list-style-type: none">• galvanized feed hopper 4-parted 2 x 2 m• electric drive 9,5 kW• lightning 2 pieces• light bar for transport by road (for tractor linkage)

MAMMUT AFM 175 5S



- ✓ patent-registered outlet ports
- ✓ practical for wet, frozen or very rough sand
- ✓ very unsensitive stirrer
- ✓ galvanized adjustment of height of the machine for pleasant working height
- ✓ accessories as per preparation
- ✓ robust angular gear with comfortable gear transmission ratio for calm and trouble-free work
- ✓ various types of propulsion

Technical data

drive	PTO-drive from the tractor – optionally with electric drive 11 kW
drum diameter	1 750 mm
capacity	1 000 l
sacks per hour	3 800
outlet ports for the workers	5
guarantee	3 years

Standard equipment	Additional equipment
<ul style="list-style-type: none"> • protective grid on the surface of the machine • PTO-drive from the tractor • mount for forklift tines series 	<ul style="list-style-type: none"> • galvanized feed hopper 4-parted 2,2 x 2,2 m • electric drive 11 kW • lightning 2 Stk. • light bar for transport by road (for tractor linkage)

combi-mixer



- ✓ combines the advantages of a concrete mixer TM 150 with a sandbag filling machine in one device
- ✓ the concrete mixer can be easily and quickly converted into a sandbag filling machine
- ✓ 2 patent-registered outlet ports
- ✓ robust and user-friendly construction



MAMMUT



MAMMUT MASCHINENBAU GES.M.B.H.

A-4942 GURTEN – Rieder Straße 9 – Tel- +43(0)7757/6701-Fax 6701-33

e-mail: office@mammut.at – Internet: www.mammut.at